

SKG-IKOB PRODUCTCERTIFICATE

527.312.15

Date of issue: 29-06-2017



Certificate holder

Cisa SpA
Via Oberdan, 42
IT-48018 Faenza (RA)
T: +39 0546 677 111
E: cisa@eu.irco.com
I: cisa.ingersollrand.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder

delivered under logo / brand:

CISA

delivered under type- and / or article number:

AP4 S series: 1.0P3S1.xx.0.xx.xx , AP4 S series: 1.0P314.xx.0.xx.xx

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized 'H' and 'A' followed by a horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

Cisa SpA
Number: 527.312.15

page 2 of 2

1. PRODUCT

euro profile cylinder

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	double or single
System:	horizontal key profile 1 row of 6 mechanical operated retainers + 2 rows of resp. 5/6 and 2/3 block elements + 1 mechanical operated pin
Material:	cylinder body: brass with various coatings
Dimension:	17 mm profile from 30 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length \geq backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furniture

3. DELIVERY

The delivery includes an installation instruction:
0.892.0341.0.00.00/A

4. PERFORMANCES

A euro profile cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-